

Diagnostic Systems for the
Heart and Lungs



Manage complex data easily

AMEDTEC *ECG pro*



Six heads:

Driven by one idea

▶ WHO WE ARE

High-tech and healthcare: AMEDTEC is continuing the work that was started fifty years ago as a national enterprise with the design of the 6-lead electrocardiograph (ECG). Since then, measuring and medical technology from the German state of Saxony has become known throughout the world.

AMEDTEC Medizintechnik Aue GmbH was founded in 1998 with this knowledge in mind.

Six engineers came together to work as development service providers, creating hardware and software for leading international manufacturers of 12-lead and Holter ECG systems.

In parallel to this, the company concentrated its efforts on the expansion of cardiopulmonary data management systems, focusing primarily on networks, interface integration, data exchange and interoperability between hospital information systems and private practices.

AMEDTEC transformed from a pure service and development company into a manufacturing company and, from 2006 onwards, became a supplier of integrated solutions. The company launched its own system – AMEDTEC *ECGpro*[®] – on the market. This technology completely revolutionises ECG diagnostics. It meets the premises of modern medicine as well as the high demands of data communication.

AMEDTEC *ECGpro*[®] is at the heart of all our products. It allows data to be recorded, analysed and exchanged for 12-lead ECGs (resting and stress test), Holter ECGs, blood pressure monitoring, ergospirometry, body plethysmography and spirometry.

In cooperation with Geratherm Respiratory, a specialist in pulmonary function diagnostics, AMEDTEC offers an entire range of products for cardiopulmonary function diagnostics. Whether used in hospitals or medical practices, AMEDTEC stands for innovation and lasting value.

▶ HOW WE SEE OURSELVES

AMEDTEC represents the innovative strength of medium-sized German companies. Living up to the tradition of ambitious inventors and developers, we are devoted to one thing: customer satisfaction. We are committed to this every single day.

The AMEDTEC system solutions and products are used for diagnosing cardiopulmonary function. We believe this to be our particular responsibility.

MEDICAL TECHNOLOGY FOR THE GOOD OF MANKIND

There's always room for improvement. We reinvest the bulk of our profits into optimising our technology or in developing new products. We work closely with our customers and with practitioners to develop powerful, yet intuitive products. It does not matter whether you are a patient, doctor or medical assistant – when it comes down to it, you need a reliable, easy-to-use application.

We therefore maintain a constant dialogue, both inside and outside the company.

LISTEN. CONSIDER.

OFFER INTEGRATED SOLUTIONS

AMEDTEC takes the requirements of users and the needs of patients seriously. This is why we provide an excellent level of service with prompt assistance from our experienced staff. You can rely on an international sales network and professional customer service. After all, we invest our knowledge entirely in medical progress.

THE IMPORTANCE OF QUALITY

AMEDTEC operates in a manner consistent with its corporate policy: All AMEDTEC products meet the strict standards of medical technology. Thus, we have based our quality management system on these – it is certified in accordance with DIN EN ISO 13485 and DIN EN ISO 9001. Our quality assurance system is certified in accordance with the European 93/42/EEC Medical Device Directive, Annex II.

After all, top quality is the sum of all details.


Contents

DATA MANAGEMENT

The data from all AMEDTEC function diagnosis modules converges in the central data management system AMEDTEC *ECGpro*®.

AMEDTEC *ECGpro*® can be flexibly integrated with the information systems used in hospitals or medical practices via HL7, DICOM and BDT/GDT.

06



RESTING ECG STRESS TEST ECG

The 12-lead resting ECG from AMEDTEC is built as a modular software system, which enables you to record and analyse both 10-second resting ECGs and longer rhythm ECGs with or without arrhythmia detection quickly and easily.

Performing an ergometry test is easy with the AMEDTEC stress test ECG system.

By adding a spirometry testing unit with respiratory analysis functions, you can easily turn the measuring station into a high-value ergospirometry testing system.

10



AMBULATORY BLOOD PRESSURE MONITORING HOLTER ECG

The AMEDTEC Holter ECG is a complete long-term ECG system with an optimal workflow. It provides a fast and accurate analysis of Holter ECG recordings made in either 3 or 12-channel mode.

The AMEDTEC *ECGpro*® Holter-RR system records up to 72 hours of ambulatory blood pressure. Thanks to the device's AutoFeedbackLogic (AFL), the patient endures only minimum discomfort.

A user guide allows you to prepare the ambulatory blood pressure recorder quickly and easily with patient data and the required monitoring protocol.


14



MONITORING AND REPORTING MODULES

The AMEDTEC software AMEDTEC *ECGpro*® is the all-rounder for recording, analysing, presenting and archiving cardiac stress and pulmonary function tests. It can be easily integrated into your hospital information system (HIS) or your practice software.

18



TECHNICAL DATA

Take a look at our product specifications, where you will find all the important technical information related to the individual devices.

20



SERVICE CONTRACT CUSTOMER SERVICE LEASING, CONTACTS


Professional customer service is part of the AMEDTEC philosophy.

We deal with your enquiries and orders promptly and offer fast and competent solutions for technical problems.

Full service: AMEDTEC equips hospitals and medical practices with measuring stations and data management systems. We also supply accessories and consumables.

Thus, our customers can plan ahead with certainty. Contact us for more information.

26



AMEDTEC Data Information System

AMEDTEC ECG^{pro} Data Management

HIGH LEVEL OF SECURITY

Benefit from the efficiency of professional data management.

AMEDTEC ECG^{pro} takes into account the sensitivity of medical diagnostics. The Microsoft SQL Server provides an advanced, solid platform for storing and recording data. All cardiopulmonary measuring stations are connected to the AMEDTEC ECG^{pro} database via high-speed data cables. Storing the data on a central server guarantees that the data is secure and that all information is available whenever it is needed. Devices that work offline synchronise automatically by replicating the data as soon as a network connection is detected. User-specific settings and the assignment of privileges or login details protect the system against unauthorised access.

FLEXIBLE INTEGRATION

Economic efficiency calls for future-proof solutions. AMEDTEC ECG^{pro} ensures communication via HL7, DICOM and GDT interfaces. The data management system is designed so that it integrates smoothly with existing HIS, picture, archiving and communication systems (PACS) or practice software environments. The AMEDTEC GDT server manages and transfers data from external systems. Data from selected ECG devices is also transferred.

SIMPLER WORKFLOWS

Would you like external analyses without the risks? With Interlink, AMEDTEC ECG^{pro} ensures the fast, secure transmission of recorded data or diagnostic reports via the internet.

Would you like to view ECG curves during the test? AMEDTEC ECG^{pro} Online transfers ongoing ECGs to all authorised workstations in real time.

AMEDTEC ECG^{pro} Workflow

MORE EFFICIENT DIAGNOSTICS


AMEDTEC simplifies the complexity of cardiopulmonary tests.

AMEDTEC ECG^{pro} Workflow directs all relevant information to the right place at the right time. It does not matter whether you work in a medical practice or hospital – the system is bi-directional, reliable and, if required, completely paperless. Examination requests can be created directly in the HIS, PACS or practice software. AMEDTEC ECG^{pro} accepts these and forwards them to the workstation or measuring station. The request is added to the worklist.


PERFECTLY ORGANISED

When the diagnosis is complete, the worklist is updated automatically. The results are forwarded immediately to the HIS, PACS or practice software. With just a few clicks, the doctor has the test results in electronic form. AMEDTEC ECG^{pro} supports case-based invoicing and enables you to archive data digitally.

DATA MANAGEMENT



WORKFLOW



CardioPart 12 Resting ECG




WITH OR WITHOUT CABLES

Whether you wish to record automatic 10-second resting ECGs or longer rhythm ECGs – the CardioPart 12 Resting ECG is ideally suited both for use in laboratories and for mobile use. The Hannover ECG Program HES[®], which has been validated by an independent test centre, is used to interpret the results.

PRODUCT DETAILS

- One-button operation
- Simply press the start button on the CardioPart 12 Blue to start the ECG recording
- Check the recording quality prior to the ECG recording
- Switch between preconfigured ECG views while recording
- Many configuration options → compile individual diagnostics programs even for geriatrics and paediatrics
- Predefined text blocks help you write the final report
- Wide selection of print formats → easy to add other formats
- Strict hygiene standards
- Integrated in the AMEDTEC ECG^{pro} data management system

CardioPart 12 Stress Test ECG



SIMPLE. SAFE. EFFECTIVE.

The CardioPart 12 Stress Test ECG scores highly for its absolute precision, intuitive menu guidance and extreme flexibility. The automatic ST, HR and rhythm monitoring is carried out during the ECG monitoring. Current cardiac events appear immediately in a separate window.

PRODUCT DETAILS

- CardioPart 12 ECG recording device with USB or Bluetooth connection
- Ideal for sports medicine → wireless data transfer (e.g. treadmill)
- Optional control of treadmill or bicycle ergometer and stress echo couch from one measuring station
- One-button operation → user is guided through the test step by step
- Check the recording quality of each electrode prior to the test
- The stress test ECG can run fully automatically → without any operator intervention
- Load values can be changed manually at any time within the automatic stress test procedure
- Print (automatic/manual) ECG sections or successive sequences during the test
- Retrospective view of the entire 12-lead ECG → analyse anomalies in context
- Automatic final report → editable, predefined text blocks
- Network-wide view of ECG curves in real time for all authorised users using AMEDTEC ECG^{pro} Online
- Configure a wide range of diagnostic programs yourself
- Create your own load profiles as a slope and/or ramp
- Wide selection of print formats → easy to add other formats
- Integrated in the AMEDTEC ECG^{pro} data management system

Holter ECG EP8



ECG PRESENTATION WITHOUT COMPROMISES

The Holter ECG EP8 is an outstanding performer within the field of long-term diagnostics. This EP820 lightweight recorder weighs less than 56 grams (including battery), ensures minimum patient discomfort and provides excellent signal quality. The analysis software is based on accurate algorithms and delivers precise measurement data. Programs developed specifically for paediatrics allow appropriate interpretation of the ECG for children.

PRODUCT DETAILS

- Easy preparation of the recorder
- Automatic patient assignment when importing the recording
- Multi-day recording (→ 7 days) without data reduction or compression deficiencies
- Rhythm analysis using parameters that can be configured specifically for ECGs
- Intelligent pacemaker analysis
- Differentiation between atrial and ventricular pacing spikes
- Risk management using ischaemia, QT and HRV analysis
- Detection of atrial arrhythmia
- Creation of automatic reports that can be edited and configured
- Integrated in the AMEDTEC *ECG_{pro}* data management system

Holter-RR Ambulatory Blood Pressure Monitoring



NON-INVASIVE DIAGNOSTICS.


Meaningful data: The Holter-RR guarantees reliable, ambulatory blood pressure monitoring. The Auto Feedback Logic (AFL) allows quiet, fast readings with low cuff pressure. Threshold tables for children and young people are integrated for precise interpretation.

PRODUCT DETAILS


- Stable ambulatory blood pressure monitoring
- Multi-day recording (up to 72 hours)
- Comparison of various test series
- Definition of multiple day and night intervals
- Fast, convenient preparation of the recorder
- Automatic patient assignment when importing the recording
- Patient-friendly monitoring thanks to adaptive cuff inflation
- Validated in accordance with the European Society of Hypertension (ESH International Protocol) and the British Hypertension Society (BHS A/A Grading)
- Integrated in the AMEDTEC *ECG_{pro}* data management system

Monitoring and Reporting Modules


CardioPart 12 Resting ECG



Electrodes application and signal quality check




Results



Ongoing ECG recording


CardioPart 12 Stress Test ECG



Ongoing ergometry with arrhythmia detection




Rhythm overview




Results table and summary

Holter ECG




Full disclosure ECG with HF trend and enlarged single beat



Heart rate variability (HRV)



Rapid detection of atrial arrhythmia



Report creation


Holter-RR



Configurable overview



Test series comparison



Change in blood pressure with early morning rise

Technical Data

CardioPart 12 Blue / Blue-P

Dynamic range	+/- 316 mV DC
Sample rate	8000 Hz [125 μs] for each of the 10 electrode channels
Resolution	1 μV/LSB [0.01 mm]
Frequency range	0 – 150 Hz
Pacemaker detection	Digital monitoring of all electrodes
Input impedance	> 50 MOhm
Electrodes check	Frequency analysis and impedance measurement
Input protection	Against defibrillator shock ¹⁾ and HF from surgery devices
Patient cable connection	15-pin D-Sub for 10-lead patient cable
Applied part	Type CF
PC interface	Bluetooth Class 1 or Class 2
Power supply	2 Mignon AA alkaline or rechargeable batteries
R wage trigger output	Via separate radio module
Dimensions	110 mm x 64 mm x 28 mm
Weight	160 g
Standards	DIN EN 60601-1; DIN EN 60601-2; DIN EN 60601-2-25; DIN EN 60601-2-51; ANSI/AAMI EC 11

CardioPart 12 USB / USB-P

Dynamic range	+/- 316 mV DC
Sample rate	8000 Hz [125 μs] for each of the 10 electrode channels
Resolution	1 μV/LSB [0.01 mm]
Frequency range	0 – 150 Hz
Pacemaker detection	Digital monitoring of all electrodes
Input impedance	> 50 MOhm
Electrodes check	Frequency analysis and impedance measurement
Input protection	Against defibrillator shock ¹⁾ and HF from surgery devices
Patient cable connection	15-pin D-Sub for 10-lead patient cable
Applied part	Type CF
PC interface	USB 2.0 (5 metre USB cable)
Power supply	Via the USB port of the PC
R wage trigger output	Via LPT port of the PC
Dimensions	95 mm x 64 mm x 28 mm
Weight	90 g
Standards	DIN EN 60601-1; DIN EN 60601-2; DIN EN 60601-2-25; DIN EN 60601-2-51; ANSI/AAMI EC 11



Supported HIS, PACS and BDT/GDT communication	CardioPart 12 Blue/USB	CardioPart 12 Blue/USB-P (specifically for medical practices)
BDT/GDT	✓	✓
HL7/DICOM	✓ (Option)	-

Available ECG options	CardioPart 12 Blue/USB	CardioPart 12 Blue/USB-P (specifically for medical practices)
<i>m</i> Resting ECG with automatic measurement	✓	-
<i>mr</i> Resting ECG with automatic measurement and rhythm ECG option	✓	✓
<i>i</i> Resting ECG with automatic measurement, interpretation and rhythm ECG option	✓	✓
<i>s</i> Resting and stress test ECG with measurement, interpretation and rhythm ECG option, ST measurement, control of ergometers and blood pressure meters	✓	✓
<i>as</i> Resting and stress test ECG with measurement, interpretation and rhythm ECG option, ST measurement, arrhythmia analysis, control of ergometers and blood pressure meters	✓	-

1) The patient cable or suction electrode system must feature a protective resistor of 10 kOhm in each of the cables. Protection against defibrillator discharge is only ensured through the use of a patient cable or suction electrode system of this type.

 **Motion PC**

CPU	Intel® Processor
Operating system	Windows® 8.1 Pro Windows® 7 Professional 64-bit
Durability	MIL-STD-810G certified IP54 certified (water, dust and splash resistant) Scratch-resistant and break-resistant Corning Gorilla® Glass display Rubberised for shock dampening Magnesium-alloy internal frame Ergonomic handle helps prevent drops
Screen	10.4" XGA (1024 x 768) View Anywhere® display with projective capacity 10-point Touch TFT FFS+ LED backlight with durable Corning Gorilla® Glass
System memory	Solid State Drive (SSD)
Integrated communications	IEEE 802.11ac Wi-Fi® and Bluetooth® 4.0
I/O ports	Docking station connector
Additional information	1D/2D barcode reader
Dimensions	256 mm x 256 mm x 24.3 mm
Weight	1.50 kg ¹
Battery	Battery life up to eight hours ²

 **Holter EP 820/EP 820-12**

Dimensions	Size	68 mm x 53 mm x 16 mm (L x W x H)
	Weight	42 g
	Operating position	Any orientation
Electrical data	Gain settings	0.5 x, 1 x and 2 x
	Connector	26 pin
	Patient cable	4, 5, 7 or 10 wire
Function	Recording channels	3 or 12
	Sensitivity	2.5 µV / LSB
	Recording	Full disclosure
	PC interface	USB 2.0 or card reader
	Sample rate	10,000/s (PM detection)
	Frequency range	0.05 Hz to 60 Hz, -3 dB
	ECG signal view	Via LCD at hook-up or on demand
	Pacemaker detection	Permanently
Battery	Battery type	1 AAA battery, 1.5 V alkaline, lithium, or NiMH
	Recording time (3 channels)	Alkaline: ≥ 96 h Lithium: ≥ 168 h
	Recording time (12 channels)	Alkaline: ≥ 48 h



Docking station with USB and LAN connectors as well as battery charger



Barcode scanner, e.g. for fast patient searches using a barcode label



 **Holter-RR**

Pressure measurement range	Systolic 60 to 290 mmHg Diastolic 30 to 180 mmHg
Accuracy	+/-3 mmHg in the range indicated
Static pressure range	0 to 300 mmHg
Pulse range	30 to 240 beats per minute
Method	Oscillometric
Measurement intervals	0, 1, 2, 4, 5, 6, 12 or 30 measurements per hour
Monitoring protocols	2 programmable and 7 fixed protocols
Storage capacity	300 measurements
Operating temperatures	+10 °C to +40 °C
Operating humidity	15% to 90%
Dimensions	128 mm x 75 mm x 30 mm
Weight	Approx. 240 g incl. rechargeable batteries
Power supply	2 Mignon AA alkaline or rechargeable batteries
Interfaces	Cable: serial interface RS232, converter for USB, Infrared, Bluetooth Class 1
Standards	DIN EN 60601-1, DIN EN 60601-2, EN 1060-1, EN 1060-3, R&TTE directive 1999/5/EC



 **medical bike**

Braking system	Processor-controlled, speed-independent eddy current brake
	Power range 5 – 1000 watts
	Adjustable in 1 watt increments
Displays	LED/LCD display
	LED display on front side
	Display unit can pivot to 180°
Configuration options	Seat height 70 – 105 cm (manual adjustment) or 70 – 102.5 cm (electrical adjustment)
	Handlebar grip infinitely adjustable with 360° rotation
	Ergonomic steering column adjustment
	Adjusting screws for floor unevenness
Dimensions	Approx. 102 cm x 56 cm x 120 cm (L x W x H)
Weight	Approx 57 kg
Rollers	Integrated rollers in the base plate for easy moving
Maximum patient weight	200 kg
Power supply	85 – 264 V / 47 – 440 Hz / 40 – 65 W (medical power supply)
Interfaces	RS-232, USB, Bluetooth
Operating conditions	
Temperature range	+10 °C to +40 °C
Relative humidity	20 % to 80 %
Safety standards	DIN EN 60601-1, DIN VDE 0750-238
Protection class	I
Applied part	Type BF
Risk class	Ila

MODELS

	Electrical saddle height adjustment	Integrated blood pressure measurement
medical bike mb-1	-	-
medical bike mb-2	-	✓
medical bike mb-3	✓	-
medical bike mb-4	✓	✓

OPTIONS/ACCESSORIES

- Ergonomic steering column adjustment
- 5.7" colour LCD display
- Bluetooth interface
- Crank shortener for children, adjustable



Service. Support. Safety.



Products. Offers. Enquiries.

Professional customer service is part of the AMEDTEC philosophy. We have built up a comprehensive service network to provide you with prompt and competent advice. AMEDTEC is represented in five locations across Germany. We work together with international sales partners to ensure our global market presence.



Remote assistance. Repairs. Replacement service.

TECHNICAL PROBLEMS REQUIRE QUICK AND SIMPLE SOLUTIONS.

AMEDTEC has set up a service hotline under +49 (0)3771 59 82 75 0 for precisely this reason. You can reach the AMEDTEC support staff on Mondays to Fridays from 7 am to 5 pm. Smaller problems can be resolved directly over the phone. For more complex problems, our support staff will be able to help you by accessing your system remotely using the TeamViewer application. Our technicians will come out to you promptly upon request.

IT IS BETTER TO PREVENT THAN TO REPAIR.

Checking your hardware and software regularly minimises the risk of technical faults or system incidents. With the AMEDTEC service contract you are on the safe side. If more extensive repair work is required, we will provide you with a replacement device.

SAFETY FIRST.

The German Medical Device Operator Ordinance requires operators of medical devices to perform technical inspections of the measuring system and technical safety inspections (STK/MTK) every two years. AMEDTEC carries out these inspections – our service technicians are authorised in accordance with DIN EN 62353.



Updates. Accessories. Financing.

KEEPING UP WITH MEDICAL TECHNOLOGY.


The AMEDTEC update service keeps your AMEDTEC *ECGpro*® up-to-date. In the AMEDTEC user training you will learn about the new software features and find out about our product improvements.

MEASURING STATION, PATIENT CABLE OR SINGLE USE FLOW SENSOR.

Full service means: AMEDTEC equips hospitals and medical practices with measuring stations and data management systems. We also supply accessories and consumables.

FLEXIBILITY WHEN IT COMES TO FINANCING.

With AMEDTEC, you can plan ahead with greater financial security. Enquire about our leasing offers or financing packages. Your terms of payment can be adapted to satisfy your needs.



SALES DIVISIONS
IN GERMANY



REMOTE ASSISTANCE

In many cases, the AMEDTEC support staff will be able to help you by accessing your system remotely. To make use of this fast and efficient option, please download the TeamViewer application from our website onto your respective PC. Provided that there is a working Internet connection at that PC, the remote support can be initiated as soon as you provide us with your individual TeamView login details.



CONTACT, SERVICE AND SUPPORT

AMEDTEC Medizintechnik Aue GmbH
Schneeberger Str. 5
08280 Aue, Germany
Contact phone no.: +49 (0)3771 59 82 70
Contact e-mail: info@amedtec.de
Service phone no.: +49 (0)3771 59 82 750
Service e-mail: service@amedtec.de
Fax no.: +49 (0)3771 59 82 790

MAINTAINING A DIALOGUE. INSIDE AND OUTSIDE.

AMEDTEC Medizintechnik Aue GmbH

Schneeberger Straße 5

08280 Aue, Germany

Tel: +49 3771 59 82 70

Fax: +49 3771 59 82 79 0

info@amedtec.de

www.amedtec.de



M0598 000-0317-2_04
Errors and omissions excepted

AMEDTEC © 2016